
BSP male cone seat x BSP swivel female O'ring (Soft Seal) 90° compact elbow

Oct-21 0633 IMP

All dimensions are imperial unless stated.






| | | T1 | T2 | B1 | B2 | L1 | O/L | LL1 | LL2 | A/F | A/F1 |
|--|----------|-----|-----|-------|-------|-------|-------|-------|-------|-------|------|
| | 05000-OR | 1/4 | 1/4 | 0.185 | 0.172 | 0.565 | 1.335 | 0.993 | 0.975 | 0.625 | 19mm |
| | 05001-OR | 3/8 | 3/8 | 0.312 | 0.271 | 0.6 | 1.52 | 1.085 | 1.158 | 0.75 | 22mm |
| | 05002-OR | 1/2 | 1/2 | 0.437 | 0.375 | 0.74 | 1.84 | 1.329 | 1.283 | 0.875 | 27mm |
| | 05004-OR | 3/4 | 3/4 | 0.625 | 0.6 | 0.82 | 2.06 | 1.44 | 1.468 | 1.125 | 32mm |
| | 05005-OR | 1 | 1 | 0.812 | 0.797 | 1.05 | 2.475 | 1.762 | 1.724 | 1.375 | 41mm |

BSP male cone seat x BSP swivel female O'ring (Soft Seal) 90° compact elbow

Oct-21 0633 METRIC

A/F dimensions are imperial unless stated.





| | T1 | T2 | B1 | B2 | L1 | O/L | LL1 | LL2 | A/F | A/F1 |
|----------|-----|-----|-------|-------|-------|-------|-------|-------|-------|------|
| 05000-OR | 1/4 | 1/4 | 4.7 | 4.37 | 14.35 | 33.91 | 25.22 | 24.77 | 0.625 | 19mm |
| 05001-OR | 3/8 | 3/8 | 7.92 | 6.88 | 15.24 | 38.61 | 27.56 | 29.41 | 0.75 | 22mm |
| 05002-OR | 1/2 | 1/2 | 11.1 | 9.53 | 18.8 | 46.74 | 33.76 | 32.59 | 0.875 | 27mm |
| 05004-OR | 3/4 | 3/4 | 15.88 | 15.24 | 20.83 | 52.32 | 36.58 | 37.29 | 1.125 | 32mm |
| 05005-OR | 1 | 1 | 20.62 | 20.24 | 26.67 | 62.87 | 44.75 | 43.79 | 1.375 | 41mm |